

(12) UK Patent Application (19) GB (11) 2 362 310 (13) A

(43) Date of A Publication 21.11.2001

(21) Application No 0011731.7

(22) Date of Filing 17.05.2000

(71) Applicant(s)
Kevin Morris
5 Verlon Close, MONTGOMERY, Powys, SY15 6SH,
United Kingdom

(72) Inventor(s)
Kevin Morris

(74) Agent and/or Address for Service
Urquhart-Dykes & Lord
Three Trinity Court, 21-27 Newport Road, CARDIFF,
CF24 0AA, United Kingdom

(51) INT CL⁷
A41D 13/08 , A44C 9/00

(52) UK CL (Edition S)
A3H H30X
A3V V1A1X

(56) Documents Cited
GB 2183990 A JP 110222703 A US 6023786 A
US 5609165 A US 4733410 A US 4689828 A
US 4423722 A

(58) Field of Search
UK CL (Edition S) A3H H30X H31B , A3V V1A1B
V1A1X
INT CL⁷ A41D 13/00 13/08 , A44C 9/00 , D04B 3/04 ,
D05B 91/04
Online : EPODOC, WPI, JAPIO

(54) Abstract Title
Finger ring protector

(57) A finger ring protector comprises a tubular member 10 of flexible or semi-rigid material eg rubber having a bulbous lower flange 12 and an enlarged diameter portion 14 to accommodate a ring. There may be a narrowed portion (16, Fig 2) above the enlarged portion which fits the finger snugly below the knuckle and a further tapering portion (20) which fits the finger above the knuckle. The member may include holes for aeration.




FIG. 1

BEST AVAILABLE COPY

GB 2 362 310 A

The claims were filed later than the filing date but within the period prescribed by Rule 25(1) of the Patents Rules 1995.

At least one drawing originally filed was informal and the print reproduced here is taken from a later filed formal copy.

-1/1-




FIG. 1




FIG. 2

Safety Device

This invention relates to a safety device for covering a ring when worn on a finger or toe, particularly but not exclusively to protect the ring from damage and/or the wearer or others from injury.

5 There are many different activities in which it is either desirable or mandatory to remove or cover up rings. For example, in sports such as rugby or football, it is mandatory to either remove or completely cover rings during a match, primarily to prevent injury to other plays. As many players
10 cannot or do not wish to remove their ring(s), it is usual for them to completely cover the ring(s) by wrapping insulating tape around their finger(s) and over the ring(s). However, this is not only time consuming but can also be uncomfortable for the player.

15 I have now devised an arrangement which seeks to overcome the problems outlined above.

 In accordance with the present invention, there is provided a device for substantially covering a ring when worn on a user's finger or toe, comprising a generally tubular
20 member which is worn over the finger and substantially covers the ring, when in use.

 Also in accordance with the present invention, there is provided a method of substantially covering a ring when worn on a user's finger or toe, comprising the steps of providing
25 a generally tubular member and sliding said tubular member over the finger so as to substantially cover the ring.

 Other activities in which it is either desirable or mandatory to remove or cover up rings include any activities involving the use of machines in which rings may get trapped
30 causing serious injury, such as industrial machine tools, industrial applications including aerospace and automotive (manufacture and service), military applications, activities

which require a relatively high level of hygiene, such as catering and medicine/surgery, and household activities such as cooking, washing up, cleaning, gardening or DIY, during which rings may be damaged or present a hygiene problem.

5 Although the device diameter of the generally tubular member may be substantially uniform along its length, the diameter of the portion of the tubular member intended to cover the ring, when in use, is beneficially of a larger diameter than the rest of the tubular member intended to cover the
10 wearer's finger below the knuckle. The larger diameter portion of the tubular member may be reinforced so as to more suitably accommodate a protruding ring, such as a dress or engagement ring.

 The tubular member is beneficially of a flexible or
15 semi-rigid material, for comfort and also to enable one size to accommodate more than one finger size. The material may be substantially waterproof, and may be provided with one or more holes for aeration, primarily to prevent discomfort caused by a build up of perspiration under the tubular member. In any
20 event, the tubular member is beneficially of a material which is hard-wearing and substantially resistant to degradation due to frequent flexing, moisture, etc.

 The lower end of the tubular member may be formed with a circumferential flange or seal which abuts the lower end of
25 the finger in a snug fit, when in use, to aid retention of the tubular member in position on the finger and over the ring.

 At least a portion of the inner surface of the tubular member is beneficially lined with a relatively smooth material, such as the material used for the inner surface of rubber
30 washing-up gloves and the like, to reduce friction and allow the tubular member to slide relatively easily over the finger.

 The tubular member is beneficially formed so that a section thereof, in use, is a snug fit above the ring and below

the user's knuckle. In one embodiment of the invention, the dimensions of the tubular member are such that it encapsulates only the ring and the base of the user's finger below the knuckle, leaving the knuckle free for maximum movement.

5 However, in another embodiment of the invention, the tubular member may be longer so as to partially or fully cover the user's first knuckle for added protection. In this case, the tubular member may have a second larger diameter portion, above the snug fitting portion above the ring and below the knuckle,

10 the second larger diameter portion accommodating the user's first knuckle and allowing at least partial movement thereof. In this case, the diameter of the tubular member preferably decreases gradually to another smaller diameter portion intended to abut the user's finger at a position above the

15 first knuckle, when in use.

The dimensions of the tubular member may be such that only a single finger can be encapsulated. Alternatively, however, the tubular member may accommodate more than one adjacent fingers. Additional separate or integral means may

20 also be provided to secure the tubular member to the finger or hand for additional security.

Tubular members may be manufactured individually, or several such members may be formed as a single piece with serrations or the like therebetween, so that a user can tear

25 one member off for use, when required.

Embodiments of the invention will now be described by way of example only and with reference to the accompanying drawings, in which:

FIGURE 1 is a cross-sectional view of apparatus

30 according to a first exemplary embodiment of the present invention; and

FIGURE 2 is a cross-sectional view of apparatus according to a second exemplary embodiment of the present

invention.

Referring to Figure 1 of the drawings, a device according to a first exemplary embodiment of the invention for substantially covering a ring (not shown) when worn on a user's 5 finger (not shown) comprises a generally tubular member 10 of a flexible or semi-rigid material, such as rubber. The lower end of the tubular member 10, i.e. the end of the tubular member 10 intended in use to be positioned on the finger below the ring, is formed with a circumferential generally bulbous 10 flange or rim 12. The tubular member 10 is shaped so as to have a relatively large diameter portion 14 between each end of the tubular member 10, so as to accommodate a ring, when in use. A portion at or adjacent the upper end 16 of the tubular member 10 is of a relatively smaller diameter so as to fit 15 against the user's finger at a position above the ring.

In use, the user simply slips the tubular member 10 over a finger carrying a ring, and slides it down until the lower end (at 12) is substantially adjacent the bottom of the finger and the ring is covered.

20 The exemplary dimensions shown in Figure 1 are in no way intended to be limiting, in the sense that the dimensions of the tubular member 10 are dependent upon many factors including the size and number of fingers to be accommodated.

Referring now to Figure 2 of the drawings, a device 25 according to a second exemplary embodiment of the invention for substantially covering a ring (not shown) when worn on a user's finger (not shown) again comprises a generally tubular member 10 with a generally bulbous rim 12 at its lower end. A relatively large diameter portion 14 is provided just above 30 the lower end (at 12) to accommodate a ring, when in use. A relatively smaller diameter portion or indentation 16 is provided so as to fit against the user's finger above the ring and below the first knuckle, when in use.

Adjacent the relatively smaller diameter portion, the diameter of the tubular member 10 increases again and then gradually decreases to form a tapered end portion 18. The upper end 20 of the tubular member 10 fits around the user's
5 finger at a position above the first knuckle, when in use.

In use, the user simply slips the tubular member 10 over a finger carrying a ring, and slides it downward until the lower end (at 12) is substantially adjacent the bottom of the finger and the ring is covered.

10 Once again, the exemplary dimensions shown in Figure 2 are in no way intended to be limiting, in the sense that the dimensions of the tubular member 10 are dependent upon many factors, including the size and number of fingers to be accommodated.

15 In summary, the present invention provides a simple device for covering one or more rings when worn on a user's finger(s). The nature of the invention is such that it can be designed and manufactured so that one size may fit many different sized fingers. Two such designs have been described
20 above with reference to Figures 1 and 2 of the drawings. However, the embodiments described above are intended to be exemplary, and many modifications and variations are envisaged, without departing from the scope of the invention.

CLAIMS

1) A device for substantially covering a ring when worn on a user's finger or toe, the device comprising a generally tubular member which is worn over the finger and substantially
5 covers the ring, when in use.

2) A device according to claim 1, wherein the diameter of the portion of the tubular member intended to cover the ring, when in use, is of a larger diameter than the rest of the tubular member intended to cover the wearer's finger below the
10 knuckle.

3) A device according to claim 2, wherein said larger diameter portion of the tubular member is reinforced.

4) A device according to any one of the preceding claims, wherein the tubular member is of a flexible or semi-rigid
15 material.

5) A device according to claim 4, wherein said material is substantially waterproof.

6) A device according to claim 5, wherein said material is provided with one or more holes for aeration.

20 7) A device according to any one of the preceding claims, wherein the lower end of the tubular member is provided with a circumferential flange or seal which abuts the lower end of a user's finger in a snug fit, when in use, to aid retention of the tubular member in position on the finger and over the
25 ring.

8) A device according to any one of the preceding claims,

wherein at least a portion of the inner surface of the tubular member is lined with a relatively smooth material so as to reduce friction and allow the tubular member to slide relatively easily over a user's finger.

5 8) A device according to any one of the preceding claims, wherein the tubular member is formed such that a section thereof, when in use, is a snug fit above the ring and below a user's knuckle.

9) A device according to any one of the preceding claims,
10 wherein the dimensions of the tubular member are such that it encapsulates only the ring and the base of the user's finger below the knuckle, when in use, leaving the knuckle free for maximum movement.

10) A device according to any one of claims 1 to 8, wherein
15 the dimensions of the tubular member are such that it encapsulates the ring and the user's first knuckle, when in use.

11) A device according to claim 10, wherein the tubular member has a second larger diameter portion, above the snug
20 fitting portion above the ring and below the knuckle, the second larger diameter portion accommodating the user's first knuckle and allowing at least partial movement thereof when in use.

12) A device according to any one of the preceding claims,
25 wherein the dimensions of the tubular member are such that only a single finger can be encapsulated.

13) A device according to any one of claims 1 to 11, wherein the dimensions of the tubular member are such that two

or more adjacent fingers may be accommodated.

14) A device for substantially covering a ring when worn on a user's finger or toe, the device being substantially as herein described with reference to the accompanying drawings.

5 15) A method of substantially covering a ring when worn on a user's finger or toe, the method comprising the steps of providing a generally tubular member and sliding said tubular member over the finger so as to substantially cover the ring.

16) A method of substantially covering a ring when worn on
10 a user's finger or toe, the method being substantially as herein described with reference to the accompanying drawings.



INVESTOR IN PEOPLE

Application No: GB 0011731.7
Claims searched: ALL

91
Examiner: R E Hardy
Date of search: 2 April 2001

Patents Act 1977 Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:
UK Cl (Ed.S): A3H (H30X H31B); A3V (V1A1B V1A1X)
Int Cl (Ed.7): A41D (13/00 13/08); A44C (9/00); D04B (3/04); D05B (91/04)
Other: Online : EPODOC, WPI, JAPIO

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
X	GB2183990 A MOHAMED : See the Figures	1,4,5,10,13
X	JP11-222703 A ORAKU : See the Figures and Abstract	1,4,5,10,12
X	US6023786 A BURNETT : See Figure 8	1,4,12,15
X	US5609165 A LAMBERT : See the Figures	1,4,5,7,9,12
X	US4733410 A GLOTKIN : See the Figures	1,4,6,7,12
X	US4689828 A BREWER : See the Figures	1,4,5,10,13
X	US4423722 A DICKMANN : See the Figures	1-5,7,9,12

X Document indicating lack of novelty or inventive step
Y Document indicating lack of inventive step if combined with one or more other documents of same category.
& Member of the same patent family

A Document indicating technological background and/or state of the art.
P Document published on or after the declared priority date but before the filing date of this invention.
E Patent document published on or after, but with priority date earlier than, the filing date of this application.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.